

ULTRAKUSTIK BOX

sound isolating socket box

ULTRAKUSTIK BOX is intended for for installation of built-in sockets and switches in soundproof structures of various types with in order to maintain tightness and soundproofing characteristics of these structures.



COMPOUND

- Massive molded plastic housing
- Embedded mounting boxes Legrand (manufactured in France)



DIMENSIONS AND PACKAGING

- Depth of mounting box: 40 mm
- Case width: 150 mm
- Overall body thickness: 45 mm

MODIFICATIONS:

- 1 GANG: socket box length 150 mm
- 2 GANG: socket box length 220 mm
- 3 GANG: socket box length 290 mm
- 4 GANG: socket box length 360 mm
- 5 GANGS: socket box length 430 mm



MOUNTING

The socket box is mounted flush with the finish sheet acoustic gypsum board.

- On the first layer of sheathing, markings for the back of the socket and cut with a jigsaw
- The body is pre-drilled for the output of the electrical cable
- The socket box is attached to the soundproof self-tapping constructions
- Drilled cable hole after installation is completed by a specialized Ultrakustik-VS



DISTINCTIVE FEATURES

- Can be used in conjunction with all types of constructions of soundproof claddings and partitions, including those with ZIPS panel system
- Has 5 different modifications
- For the convenience of filling the front panel treated with special primer
- Universal design device socket box is compatible with most modern types and sizes of sockets and switches

SCHEMES OF SOCKET MODIFICATIONS:

