




WALL SOUNDPROOFING

FRAMELESS CLADDING USING ZIPS SANDWICH-PANELS

ZIPS-III-ULTRA

MAX LOAD WITHOUT INSERTS  35 kg/r.m. CONSTRUCTION THICKNESS  55 mm



When applied?

- If you need maximum effect with the smallest thickness.
- Saves from noises of average volume - conversations, TV, barking dogs, crying children.
- The construction is recommended for gypsum, brick and concrete walls, partitions, as well as reinforced concrete floors.

ZIPS-III-ULTRA 3rd Generation Frameless Soundproofing System


-  Fireproof material
-  Certified
-  Has a European certificate
-  Passed acoustic tests

$\Delta R_w \approx 18$ dB additional airborne noise insulation

$R_w \approx 68$ dB airborne noise insulation index for the entire construction when mounted on a 120 mm thick sand-lime brick wall




- 1** ZIPS-III-Ultra sandwich-panel 1200x600x42 mm with a mounting kit average consumption per 1 m² = 1.5 pcs.



- 2** Gypsum plasterboard sheet 2000 x 1200 x 12,5 mm average consumption per 1 m² = 0.42 pcs.



- 3** Ultrakustik VS silicone neutral sealant 290 ml cartridge average consumption per 1 m² = 0.4 pcs.



- 4** Ultrakustik TAPE M100 vibration damping spacer roll 30m width 100mm thickness 4 mm (3 m²) average consumption per 1 m² = 0.73 pcs.



Approximate cost of the construction, based on m²

€/m²



INSTALLATION MANUAL

ZIPS-III-Ultra panels are attached to the wall only through the existing vibration units using plastic dowels.

If the panel is installed as a whole (without cutting) on an insulated wall, then installation is carried out using only six attachment points, the central attachment points are not used.

The ends of the sandwich-panels must adjoin the side walls and the ceiling through two layers of Ultrakustik TAPE vibration damping spacer. The tape is glued and fixed with Ultrakustik-Sealant.

The head of the screw should be screwed into the vibration unit no deeper than 1-2 mm from the level of the front side of the panel.

If the panel is cut, then all available attachment points are used for installation. Cuttings less than 250 mm are not used in the installation.

Upon completion of installation, the joints between the sandwich-panels are treated with Ultrakustik VS. The finishing layer of gypsum plasterboard sheets 12.5 mm thick is fixed to the resulting surface. Sheets must adjoin to the adjacent surfaces through 2 layers of Ultrakustik TAPE vibration damping spacer as well.

Excessively protruding Ultrakustik TAPE is cut flush with the finishing layer of gypsum plasterboard sheets. Seams are filled with Ultrakustik VS vibro-acoustic silicone sealant.




SOUNDPROOFING OF THE CEILINGS

FRAMELESS CLADDING USING ZIPS SANDWICH-PANELS

ZIPS-III-ULTRA

MAX LOAD WITHOUT INSERTS 6 kg/m²

CONSTRUCTION THICKNESS 55 mm



When applied?

- If you need maximum effect with the smallest thickness.
- Saves from noises of average volume - conversations, TV, barking dogs, crying children.

ZIPS-III-ULTRA

3rd generation soundproofing frameless system

- Fireproof material
- Certified
- Has a European certificate
- Passed acoustic tests

$\Delta R_w \approx 18$ dB additional airborne noise insulation

$R_w \approx 67$ dB airborne noise insulation index of the entire structure




1 ZIPS-III-Ultra sandwich-panel 1200x600x42 mm with a mounting kit average consumption per 1 m² = 1.5 pcs.



2 Gypsum plasterboard sheet 2000 x 1200 x 12,5 mm average consumption per 1 m² = 0.42 pcs.



3 Ultrakustik VS, silicone neutral sealant 290 ml cartridge average consumption per 1 m² = 0.4 pcs.



4 Ultrakustik TAPE M100, vibration damping spacer roll 30m, width 100mm thickness 4 mm [3 m²] average consumption per 1 m² = 0.73 pcs.



Approximate cost of the construction, based on m²

€/m²

INSTALLATION MANUAL

ZIPS-III-Ultra panels are fixed to the ceiling through 8 vibration units. Metal anchor screws from the mounting kit are inserted into the two central vibration units. Shortened anchor screws are used for mounting on hollow slabs.

The head of the screw should be screwed into the vibration unit no deeper than 1-2 mm from the level of the front side of the panel.

For the first panel, adjacent to the walls, the ridges are cut along the short and long sides, for the next panels of the first row - only along the long side.

The ends of the sandwich-panels must adjoin the side walls through two layers of Ultrakustik TAPE vibration damping spacer. The tape is glued and fixed with Ultrakustik VS sealant.

If the panel is cut, all available attachment points are used for installation. Cuttings less than 250 mm are not used in the installation.

The joints between the sandwich-panels are treated with Ultrakustik VS. The finishing layer of gypsum plasterboard sheets 12.5 mm thick is fixed to the resulting surface. Sheets must adjoin to the walls through 2 layers of Ultrakustik TAPE vibration damping spacer.

Excessively protruding Ultrakustik TAPE is cut flush with the finishing layer of gypsum plasterboard sheets. Seams are filled with Ultrakustik VS vibroacoustic sealant.